

SZ1820 Cable Pull**Main Features**

- Suitable for customized installation of analog or digital encoders of 58 mm diameter.
- Resolution: depending on the encoder
- Easy installation
- Rugged aluminum housing
- High noise immunity
- Customized special designs available

Electrical date

Potentiometric output	1 kΩ (Other values on request)
Analog output	0 ... 10 V or 4 ... 20 mA
Resolution	Depending on the encoder

Technical date - Mechanical data

Measuring range	0 to 20000 mm(SZ1820-M) 0 to 20000 mm(SZ1820-A)
Linearity	+ / - 0.05% of ultimate value
Circumference of micrometer drum	500 mm / revolution
Acceleration	2 M/S ²
Spring return	10N/15N
Measuring wire diameter	1 mm
Speed of adjustment	5m/s
Reproducibility	equal to resolution
Casing material	Aluminium 2017A
Material of measuring wire	Stainless steel 316L
IP code of casing	IP67(SZ1820-M) IP65(SZ1820-A)
Operating temperature	-20°C to +80°C
Storage temperature	-40°C to +80°C
Lifetime	100 000 cycles



Compact sensor for industrial use

The cable control sensor of the series SZ1820-A is ideal for the measurement of linear movements and positioning in industrial applications. The compact design allows an easy assembly. The robust aluminum housing in combined with our high production quality enables an accurate measurement even at hardly accessible measuring points.

Order code (6 mm shaft diameter): SZ1820-M-20000-6

Order code (10 mm shaft diameter): SZ1820-M-20000-10

SZ1820-analog

